

TECHNICAL DATASHEET

Crossweave Tape

Product quality inspection report

① Routine inspection ② Sample inspection ③ Return inspection ④ Receiving inspection
⑤ Delivery inspection

Product name	Crossweave Filament Tape
Size	48mm*50m
Temperature	23°C
Inspection item	Inspection result
Sample product structure	Polyester film/Crossweave filament/Hot melt glue
Back raw material name	Cross fibreglass yarn
Total thickness (UM)	175-180 ± 10um
Tensile strength	300N/25MM (QB7753-87)
Adhesive Type	Hot melt
Temperciance (BALL)	≥19# (GB/T4852-84)
The Sticky Force (H)	≥12 (GB/T4851-84)
180 degrees stripping force (N/25mm)	≥15 (GB/T2790-1995)
T solution volume force	1.5N/25mm (Q/320281NPB01)
Separating effect	GOOD
Temperciance	GOOD
Appearance (no viscose, no black side)	NO
Appearance (cut neat, wireless head)	GOOD
Conclusion	Inspection qualified
All data were measured data. Not for guarantee, for reference ONLY	

Important

The information contained herein is produced in good faith and is believed to be reliable but is for guidance only. Fosseway and its agents cannot assume liability or responsibility for results obtained in the use of its products by persons whose methods are outside or beyond our control. It is the users responsibility to determine the suitability of any of the products and methods of use or preparation prior to use mentioned in our literature and furthermore the users responsibility to observe and adopt such precautions as may be advisable for the protection of personnel and property in the handling and use of any of our products. Sellers & Manufacturers only obligation shall be to replace the product proven to be defective.