

# **TECHNICAL DATASHEET**

## **Original Sticky Tape**



### **DESCRIPTION**

Polypropylene film coated with a high tack acrylic adhesive system. Available in clear, brown and fragile. They are recommended for general purpose box sealing applications.

### **Technical Properties**

	<u>Value</u>	<u>Unit</u>
Carrier Thickness	23	micron
Adhesive Thickness	17	micron
Total Thickness	40 ±1	micron
Tensile Strength MD	100	N/25mm
Elongation at Break MD	215	%
Peel Adhesion	>6.5 >7.2	N/25mm > 24 hours N/25mm > 60 hours
Tack	>6.5#10cm >20#7.5cm	J.Dow Method
Test Temperature	25	° C
Test Relative Humidity	60%	

### **Important**

The information contained herein is produced in good faith and is believed to be reliable but is for guidance only. N°1 Tape and its agents cannot assume liability or responsibility for results obtained in the use of its products by persons whose methods are outside or beyond our control. It is the users responsibility to determine the suitability of any of the products and methods of use or preparation prior to use mentioned in our literature and furthermore the users responsibility to observe and adopt such precautions as may be advisable for the protection of personnel and property in the handling and use of any of our products. Sellers & Manufacturers only obligation shall be to replace the product proven to be defective.