

Product Description

Rhino Cold Weather Aluminium Foil Tape is a dead soft aluminium foil coated with a cold weather solvent acrylic pressure sensitive adhesive.

Applications

Fibre and foil backed insulation boards, ventilation ducts in heat and air conditioning applications. Vapour seals in various industries, masking and patching.

Features & Benefits

Excellent in challenging conditions such as low temperatures and humidity applications Soft foil conforms to irregular surfaces

Low application temperature of minus 20°c

Sticks well to low surface energy substrates

Particularly suited to cold weather conditions

Certified to BS476 part 6 & 7 Class "O" standard

Technical Performance

recinited removinding			
Description	Units	Value	Test method
Foil thickness	mm	0.030	ASTM D3652
Total thickness	mm	0.070	ASTM D3652
Adhesion to steel	N/25mm	15	ASTM D3330
Tack rolling ball	cm	5	ASTM D3121
Tensile strength	N/25mm	45	ASTM D3759
elongation	%	3	ASTM D3759
Service temp	°c	-35 - +120	-
Application temp	°c	-20 - +40	-

Declaration of Conformity Information

Class "O" approval

Tested in accordance with BS476: Part6:1989 +A1:2009 and BS476: Part7:1997

REACH SVHC Status

NO SHVC present according to candidates list of 16th Jan 2020

RoHS Compliance Status

Yes

Storage Details

Shelf life recommended 12 months from date of despatch at the moderate temperature and humidity environment.

The information supplied is accurate to the best of Fossewaytapes & Fixings Ltd knowledge and is based upon all current data available to it. Properties quoted are typical and do not therefore constitute a specification. Customers must complete their own assessment of the product for its intended application under their own conditions. Our technical advice is to be regarded as an expression of opinion only and although such advice is given in good faith, it shall not, in any circumstances, be regarded as the basis of or as being a representation or statement of fact. This applies also where propriety or protective rights of third parties are involved. Any liability arising in respect of our products will be strictly limited to the value of those products charged to the customer and shall not extend to any consequential loss whatsoever and howsoever arising. This document does not form part of any contract with a customer (02/05/13)