

**Product Description**

. White impregnated crepe paper tape with clear synthetic rubber resin adhesive (solvent free)

**Applications**

Mainly used for paint masking, holding, bundling, and sealing of a vast number of jobs.

**Features & Benefits**

Provides a good instant adhesion to a wide variety of surfaces

East tear

Excellent conformability

Easy curving

**Technical Performance**

Description	Units	Value	Test Method
Total thickness	mm	0.114 ± .02mm	AFERA 5006
MD tensile strength	N/cm	80 ± 15	AFERA 5004
MD elongation at break	%	8 ± 2%	AFERA 5004
Adhesion to steel plate	N/cm	>7	AFERA 5001

**Declaration of Conformity Information** Not Applicable

**REACH SVHC Status** – NO SHVC present according to candidates list of 16<sup>th</sup> Jan 2020

**RoHS Compliance Status** – Not Applicable

**Storage Details**

Shelf life recommended 12 months from date of despatch at the moderate temperature and humidity environment.

The information supplied is accurate to the best of Fosseway Tapes & Fixings Ltd knowledge and is based upon all current data available to it. Properties quoted are typical and do not therefore constitute a specification. Customers must complete their own assessment of the product for its intended application under their own conditions. Our technical advice is to be regarded as an expression of opinion only and although such advice is given in good faith, it shall not, in any circumstances, be regarded as the basis of or as being a representation or statement of fact. This applies also where propriety or protective rights of third parties are involved. Any liability arising in respect of our products will be strictly limited to the value of those products charged to the customer and shall not extend to any consequential loss whatsoever and howsoever arising. This document does not form part of any contract with a customer (02/05/13)