

Technical Data Sheet 4120 D/S PVC

**Product Description**

Double sided PVC carrier coated with a white synthetic rubber based adhesive, supplied with white silicone liner.

**Applications**

PVC film splices and for general applications

**Features & Benefits**

High initial tack

**Application notes**

Apply with a firm pressure to clean, non-porous surfaces. Test an inconspicuous area before use to determine suitability

**Technical Performance**

Description	Units	Value	Test Method
Total thickness	mic	170	Digital calliper
180° Peel	N/cm	9.0	AFERA 5004
Elongation at break	%	4	AFERA 5004
Tensile strength	N/cm	30	AFERA 5004
Static shear	hrs	30	FTM 8su acciaio
Rolling ball	cm	3	PSTC 6
Performance Temperature	°c	Min -10 max +50	-

**Declaration of Conformity Information**

**REACH SVHC Status** – NO SVHC present according to candidates list of the **UK 25/06/20 & EU 17/01/22**

**RoHS Compliance Status** – Not Applicable

**Storage Details**

Shelf life recommended 12 months from date of despatch at the moderate temperature and humidity environment.

The information supplied is accurate to the best of Fossewaytapes & Fixings Ltd knowledge and is based upon all current data available to it. Properties quoted are typical and do not therefore constitute a specification. Customers must complete their own assessment of the product for its intended application under their own conditions. Our technical advice is to be regarded as an expression of opinion only and although such advice is given in good faith, it shall not, in any circumstances, be regarded as the basis of or as being a representation or statement of fact. This applies also where propriety or protective rights of third parties are involved. Any liability arising in respect of our products will be strictly limited to the value of those products charged to the customer and shall not extend to any consequential loss whatsoever and howsoever arising. This document does not form part of any contract with a customer (02/05/13)