



EUROCEL MSK 60

Short description:

Masking tape for wall-painting on building sites.

Product Data

Backing:	59 g/m ² natural white saturated crepe paper
Adhesive:	Dry natural rubber and resins solvent based
Total thickness	0.125 mm
Adhesion to steel	4 N/25mm
Tensile strength MD	75 N/25mm
Elongation at break	8.5 %
Temp. Resistance	80 °C (30 min)

Application

Masking tape suitable for wall-painting on building and construction sites, industrial and car repair applications when temperature does not exceed 80°C.

Features	Benefits
Dry natural rubber and resins solvent based adhesive	<ul style="list-style-type: none">➤ Good adhesion even on irregular surfaces➤ Heat resistant up to 80°C (30 minutes)➤ Easy removal without adhesive residue, if removed as soon as paint is dry.
Saturated paper backing	<ul style="list-style-type: none">➤ Well conformable to most shaped surfaces➤ Compatible with most common paints and lacquers➤ Removable without breaking➤ Hand tearable

Product shelf life and storage: 12 months, based on the product being stored at 23°C/50% relative humidity out of direct sunlight.

SICAD S.p.A., Via Caduti della Liberazione, 57 21040 Uboldo (VA) - ITALY
Tel.+39 02 96412.1; Fax +39 02 96412322 export market; Fax +39 02 96780832 domestic market;
E-mail: info@eurocel.it - www.eurocel.it - www.sicadgroup.com

This information is given to the best of Sicad's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss