



EUROCEL MSK 80

Short description:

Masking tape for automotive repair workshops

Product Data

Backing:	58 g/m ² yellow saturated crepe paper
Adhesive:	Dry natural rubber and resins solvent based
Total thickness	0.135 mm
Adhesion to steel	4.5 N/25mm
Tensile strength MD	85 N/25mm
Elongation at break	9 %
Temp. Resistance	110 °C (30 min), suitable for 80°C oven drying

Application

Masking tape suitable for applications requiring high temperature resistance

Features	Benefits
Dry natural rubber and resins solvent based adhesive	<ul style="list-style-type: none">➤ Good adhesion even on irregular surfaces➤ High performance even in overlapping and with masking paper applied➤ Heat resistant up to 110°C (30 minutes)➤ Usable even for refinishing with Infra Red lamps➤ Resistant to paint and lacquer thinners➤ Easy removal without adhesive residue
Saturated paper backing	<ul style="list-style-type: none">➤ The yellow colour allows even shading, creating clear contrast with most frequent colours➤ Well adaptable to most shapes➤ Compatible with most common paints and lacquers➤ Removable without breaking➤ Hand tearable

Product shelf life and storage: 12 months, based on the product being stored at 23°C/50% relative humidity out of direct sunlight.

SICAD S.p.A., Via Caduti della Liberazione, 57 21040 Uboldo (VA) - ITALY
Tel.+39 02 96412.1; Fax +39 02 96412322 export market; Fax +39 02 96780832 domestic market;
E-mail: info@eurocel.it - www.eurocel.it - www.sicadgroup.com

This information is given to the best of Sicad's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss