

0038 Builder tape

### **Product Description**

Soft plasticised PVC tape with a pressure sensitive rubber based adhesive.

### **Applications**

Surface protection for general materials in building trade, ideal for masking aluminium, UPVC and painted wooden window and door frames

### **Features & Benefits**

Weather resistant

Limited UV-resistant

Application temperature -10°C – 80°C

### **Technical Performance**

Description	Units	Value	Test Method
Total thickness	mm	0.13	ASTM D-1000
Adhesion to steel	Kg/cm	0.14	ASTM D-1000
Elongation at break	%	180	ASTM D-1000
Tensile strength	Kg/cm	2.00	ASTM D-1000

### **Declaration of Conformity Information**

**REACH SVHC Status** – CONTAINS Bis (2-ethyl(hexyl)phthalate) (DEHP) CAS 117-81-7

**RoHS Compliance Status** – Not Applicable

### **Storage Details**

Shelf life recommended 1 year from date of despatch at the moderate temperature and humidity environment.

The information supplied is accurate to the best of Fosseway Tapes & Fixings knowledge and is based upon all current data available to it. Properties quoted are typical and do not therefore constitute a specification. Customers must complete their own assessment of the product for its intended application under their own conditions. Our technical advice is to be regarded as an expression of opinion only and although such advice is given in good faith, it shall not, in any circumstances, be regarded as the basis of or as being a representation or statement of fact. This applies also where propriety or protective rights of third parties are involved. Any liability arising in respect of our products will be strictly limited to the value of those products charged to the customer and shall not extend to any consequential loss whatsoever and howsoever arising. This document does not form part of any contract with a customer (02/05/13)