



Rev Oct 2013

**Data Sheet: Ref 66696**

**DOUBLE SIDED POLYETHYLENE FOAM TAPE**

TECHNICAL DETAILS	TYPICAL VALUE	UNITS
Adhesive type	Rubber/resin	
180° Peel adhesion:	>internal strength of foam	N/m
Foam density	67	Kg per cu.m
Shore hardness	44	00 scale
Force to compress by 25%	40	kPa
Release liner	White glassine	
Liner release	10	N/m
Tensile strength	400	kPa
	265	kPa
Elongation at break	130	%
	125	%
Service temperature	-10 to +70	°C
Recommended application temp.	+5 to +25	°C
UV resistance	Moderate	
Fungi resistance	Excellent	
Weather resistance	Moderate	
Shelf life	12	Months

**Test methods BS3924**

*Important Notice*

*All Fosseway products are subjected to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning Fosseway products is based upon research, which the Company believes to be reliable, but some information does not constitute a warranty. Because of the variety of possible uses for Fosseway products and continuing development of new uses, the purchaser should carefully consider the fitness and performance of the product for each intended use and the purchaser assumes all risks in connection with such use. Seller shall not be liable for damages in excess of the purchase price of the product nor for incidental nor consequential damages. All specifications are subject to change without prior notice.*