

N.E.C. Approved Exhibition Carpet Tape Double-sided Peel-Perm LDPE Tape

Description	The tape is a printed white 60 micron low density polyethylene film carrier. It is	
	coated on the open side with a low-tack peel able adhesive and on the closed side with a high-tack permanent adhesive, with an 80gsm differential white glassine release liner, which is sideways-tearable.	
Construction	Carrier:	60μ printed white low density polyethylene
	Adhesive open side:	WM800 modified acrylic peel able
	Adhesive closed side:	WM1070 pure acrylic permanent
	Release liner:	80gsm two side siliconised white glassine 2:1
	Thickness (carrier & adh):	0.108mm
	Carrier Thickness:	0.060mm
	Adhesive colour:	Clear
Typical Application	on The tape is ideally suited for	r temporary carpet-laying, as at exhibitions.
		Y Y Y Y Y Y Y Y Y Y Y Y Y Y Y Y Y Y Y
Application	to the floor, which must permanent adhesive on to	ch is exposed as the tape is wound off the roll) is applied be clean, and the release liner removed to expose the which the underside of the carpet is firmly placed. Then therefore be removed without leaving residue.
Application Typical Physical Properties	to the floor, which must permanent adhesive on to peelable side to the floor can	ch is exposed as the tape is wound off the roll) is applied be clean, and the release liner removed to expose the which the underside of the carpet is firmly placed. Then therefore be removed without leaving residue. values and should not be regarded as maximum or
Typical Physical	to the floor, which must permanent adhesive on to peelable side to the floor car. These figures are average	ch is exposed as the tape is wound off the roll) is applied be clean, and the release liner removed to expose the which the underside of the carpet is firmly placed. Then therefore be removed without leaving residue. values and should not be regarded as maximum or fication purposes.
Typical Physical	to the floor, which must permanent adhesive on to peelable side to the floor car. These figures are average minimum values for specific Peel Adhesion Steel (24 hours)	ch is exposed as the tape is wound off the roll) is applied be clean, and the release liner removed to expose the which the underside of the carpet is firmly placed. Then therefore be removed without leaving residue. values and should not be regarded as maximum or fication purposes. The state of the carpet is firmly placed.

Warranties

Shelf Life

All statements, technical information and recommendations about **Fosseway tapes** products are based on tests believed to be reliable but do not constitute a guarantee or warranty. All products are sold on the basis that the purchaser shall make their own tests to determine the suitability of such products for their particular applications and uses, and that the purchaser assumes all risks and liabilities for the results of the use of the products, including use in accordance with the seller's recommendations. No salesman, representative or agent of **Fosseway tapes** is authorised to give any guarantee, warranty or make any representation contrary

to

the

above.

12 months PSMA conditions