

### Product Description

3 Years polyester material commercial grade class 1

### Applications

Ideal for the temporary road sign market, safety markings & barrier and advisement etc.

### Features & Benefits

Strong perfect for die cutting

### Technical Performance

Description	Units	Value	Test Method
Total thickness	mm	0.225	Digital calliper
Film thickness	Mm	0.070	Digital calliper
Adhesive thickness	mm	0.030	Digital calliper
Release paper	mm	0.125	Digital calliper
Operation temperature	°c	20-28	
Working temperature	°c	-20 -60	

### Colour chromaticity

Standard light source : D65, Observation condition: 45/0, Observation angle: 2°						
Colour	Color Chromaticity				Luminance Factor	
	x	y	x	y		
White	0.350 0.360	0.300 0.310	0.285 0.325	0.335 0.375	≥0.27	
Yellow	0.545 0.454	0.464 0.534	0.427 0.483	0.487 0.423	0.16 – 0.40	
Red	0.690 0.310	0.658 0.342	0.569 0.341	0.595 0.315	0.03 – 0.10	
Green	0.007 0.703	0.026 0.399	0.177 0.362	0.248 0.409	0.03 – 0.10	
Blue	0.078 0.170	0.137 0.038	0.210 0.160	0.150 0.220	0.01 – 0.10	

### Coefficient of retro-reflection

Observation Angle	Entrance Angle	White	Yellow	Red	Green	Blue
0.2°	-4°	20	12	5	4	2.2

The information supplied is accurate to the best of Fosseway Tapes & Fixings Ltd knowledge and is based upon all current data available to it. Properties quoted are typical and do not therefore constitute a specification. Customers must complete their own assessment of the product for its intended application under their own conditions. Our technical advice is to be regarded as an expression of opinion only and although such advice is given in good faith, it shall not, in any circumstances, be regarded as the basis of or as being a representation or statement of fact. This applies also where propriety or protective rights of third parties are involved. Any liability arising in respect of our products will be strictly limited to the value of those products charged to the customer and shall not extend to any consequential loss whatsoever and howsoever arising. This document does not form part of any contract with a customer (02/05/13)

**Declaration of Conformity Information**

**REACH SVHC Status** – NO SHVC present according to candidates list of 15<sup>th</sup> Jan 2019

**RoHS Compliance Status** – Not Applicable

**Storage Details**

Shelf life recommended 12 months from date of despatch at the moderate temperature and humidity environment.

The information supplied is accurate to the best of Fossewaytapes & Fixings Ltd knowledge and is based upon all current data available to it. Properties quoted are typical and do not therefore constitute a specification. Customers must complete their own assessment of the product for its intended application under their own conditions. Our technical advice is to be regarded as an expression of opinion only and although such advice is given in good faith, it shall not, in any circumstances, be regarded as the basis of or as being a representation or statement of fact. This applies also where propriety or protective rights of third parties are involved. Any liability arising in respect of our products will be strictly limited to the value of those products charged to the customer and shall not extend to any consequential loss whatsoever and howsoever arising. This document does not form part of any contract with a customer (02/05/13)