## TECHNICAL DATA SHEET

## TW60TWU Message Tape

White low-noise polypropylene tape printed with high-visibility warning message

**FOSSEWAY** TAPES AND FIXINGS LTD

| -    |     |     |    |
|------|-----|-----|----|
| Prod | uct | dat | :α |

~ printed message

**Product description** 

- ~ backing film
- ~ film thickness
- ~ adhesive type
- ~ adhesive weight
- ~ tape width
- ~ tape length

## **Technical data**

- ~ initial tack
- ~ peeling adhesion
- ~ shear value on steel
- ~ tensile strength
- ~ elongation at break

## Storage & application data

- ~ temperature
- ~ optimum humidity
- ~ optimum storage
- ~ application temperature

3.5cm (ASTM D3121M) 6.3N/inch (ASTM D3330M) >24 hours (ASTM D3654M) 75.0N/inch (ASTM D3759) 105% (ASTM D3759)

**Bi-axial oriented polypropylene** 

Pressure sensitive, water based acrylic

20gsm +/-6% acceptable tolerance (ASTM D3652)

Optimum +25°C, minimum +15°C, maximum +65°C 65% < 6 months, away from extreme temperature/humidity and direct sunlight

Between +18°C and +65°C

THIS WAY UP

50mm 66mtr

28mu (ASTM D3652)

All information and recommendations are provided to the best of our knowledge, on the basis of our practical experience.

Nevertheless we can make no warranties, expressed or implied, including but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is therefore responsible for determining whether the product is fit for a particular purpose and suitable for the user's method of application.