

Technical Data Sheet D/S Cloth Tape

**Product Description**

Double sided white cotton cloth tape coated with natural rubber resin adhesive supplied with brown silicone glassine paper.

**Applications**

Suitable for permanent or temporary carpet laying at exhibitions and domestic applications.

**Features & Benefits**

Excellent adhesion to all surfaces and shapes  
 Easy and clean removal  
 Hand tearable

**Technical Performance**

Description	Units	Value	Test Method
Total thickness	mic	200	PSTC-133 /ASTM D 3652
Adhesion to steel	N/25mm	25	PSTC-101 /ASTM D 3330
Rolling Ball	cm	1	PSTC-6 / ASTM D 3121
Tensile strength	N/25mm	88	PSTC-131 / ASTM D 3750
Service temperature	°c	-20 - +100	-
Application temperature	°c	+10 - 40	-

**Declaration of Conformity Information** Not Applicable

**REACH SVHC Status** – NO SHVC present according to candidates list of 16<sup>th</sup> Jan 2020

**RoHS Compliance Status** – Yes

**Storage Details**

Shelf life recommended 12 months from date of despatch at the moderate temperature and humidity environment.

The information supplied is accurate to the best of Fossewaytapes & Fixings Ltd knowledge and is based upon all current data available to it. Properties quoted are typical and do not therefore constitute a specification. Customers must complete their own assessment of the product for its intended application under their own conditions. Our technical advice is to be regarded as an expression of opinion only and although such advice is given in good faith, it shall not, in any circumstances, be regarded as the basis of or as being a representation or statement of fact. This applies also where propriety or protective rights of third parties are involved. Any liability arising in respect of our products will be strictly limited to the value of those products charged to the customer and shall not extend to any consequential loss whatsoever and howsoever arising. This document does not form part of any contract with a customer (02/05/13)