



831 VIBAC® BOPP BOX SEALING TAPE 831

This Superior Performance packaging tape was designed for carton sealing, splicing, bundling, and other ultra demanding packaging applications. It offers super strength adhesive power in the heaviest applications.

PROPERTIES			
Total thickness micron	72 micron	Total thickness mils	2.830 mils
Business	Industrial Professional	Industry	Bundling Carton Sealing Splicing
Backing Type	BOPP	Backing thickness micron	50 micron
Adhesive type	Synthetic Rubber	Color	Tan
Tensile strength kg/cm	8,03 kg/cm	Elongation at break	200 %
Adhesion to steel g/cm	611,8 g/cm	Rolling ball test (RBT) cm	<2 cm
Shear on cardboard	>200 hours	Backing thickness mils	1.970 mils
Tensile strength lb./inch	45.000 lb./inch	Adhesion to steel oz./inch	56 oz./inch
Rolling ball test (RBT) inch	<0.78 inch	Service Temperature F° (Min / Max)	30/140 °F
Service Temperature C° (Min / Max)	(-2)/60 °C	Application Temperature F° (Min / Max)	50/110 °F
Application Temperature C° (Min / Max)	(10)/43 °C	Available width	72.000 mm 48.000 mm 36.000 mm 144.000 mm 96.000 mm
Available length	50.000 m 100.000 m 55.000 m	Packaging type	6 rolls flat pack