



Product Description

Economy grade polyethylene laminated cloth coated with a synthetic rubber adhesive.

Applications

Designed as a general purpose cloth tape for a full range of industrial and construction applications such as sealing, protection, insulating, repairs, short term masking and bundling.

Features & Benefits

- Good water resistance
- Good adhesion and strength
- Flexible and conformable

Technical Performance

Description	Units	Value	Test Method
Total weight	grs/sqm	180 ±10%	ISO 536
Total thickness	mm	0.195 ±10%	AFERA 5006
MD tensile strength	N/cm	>32	AFERA 5004
MD elongation at break	%	>10	AFERA 5004
Adhesion to steel plate	N/cm	>8	AFERA 5001
Rolling ball tack	cm	<0.5	PSTC 6

Declaration of Conformity Information

REACH SVHC Status – NO SHVC present according to candidates list of the **UK 25/06/20 & EU 19/01/21**

RoHS Compliance Status – Not Applicable

Storage Details

Shelf life recommended 1 year from date of despatch stored in moderate temperature and humidity environment.

The information supplied is accurate to the best of Fossewaytapes & Fixings Ltd knowledge and is based upon all current data available to it. Properties quoted are typical and do not therefore constitute a specification. Customers must complete their own assessment of the product for its intended application under their own conditions. Our technical advice is to be regarded as an expression of opinion only and although such advice is given in good faith, it shall not, in any circumstances, be regarded as the basis of or as being a representation or statement of fact. This applies also where propriety or protective rights of third parties are involved. Any liability arising in respect of our products will be strictly limited to the value of those products charged to the customer and shall not extend to any consequential loss whatsoever and howsoever arising. This document does not form part of any contract with a customer (02/05/13)