



Sicad s.p.A.

Via Caduti della Liberazione, 57
21040 Uboldo (VA) – Italia
Tel: +39 02 964121 Fax: +39 02 96412294
Web: www.eurocel.it

PRODUCT INFORMATION

EUROCEL ECOPACK 15

DESCRIPTION

Paper carton sealing tape for packaging.

PRODUCT DATA

| | |
|-----------------|---|
| Backing | 58 g/m ² saturated crepe paper; brown or white |
| Adhesive | Dry natural rubber and resins based |

| | Unit | Value | Method |
|----------------------------|--------|-------|----------|
| Total thickness | mm | 0.110 | PSTC 133 |
| Adhesion to steel | N/25mm | 3.3 | PSTC 101 |
| Tensile strength MD | N/25mm | 85 | PSTC 131 |
| Elongation at break | % | 7 | PSTC 131 |
| Temp. Resistance | °C | 60°C | = |

APPLICATION

Paper carton sealing tape for standard packaging. Printable (not in negative) or available printed up to 3 colours (30% max printable surface). Tape must be applied at room temperature.

| Features | Benefits | |
|--|--|---|
| Dry natural rubber and resins based adhesive | ✓ Good adhesion even on different types of cardboard | ✓ Good adhesion even if stored in cold temperature after closing |
| Saturated paper backing | ✓ Resistant to box shock ✓ Hand tearable | ✓ Identifies pilferage (as damaged cartons would be recognized if resealing were attempted) |

CONDITIONS OF USE AND CONFORMITY

Product shelf life and storage: 12 months; suggested storage temperature shall range from 15°C to 25°C with max. Printed rolls with length more than 50 meters: 3months of shelf life, relative humidity of 65%. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperatures are lower than suggested, it is always required to recondition the tape at normal temperature before use. This information is given to the best of Sicad's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss.

PA016EN_REV06_ECOPACK15

Società Italiana Cellophane Adesivo
P.I. e C.F. IT 00220060123
Iscrizione R.E.A. Varese n. 129175
Reg. Imprese Varese n. 00220060123
Capitale Sociale € 15.000.000 i.v.