

**Product Description**

Clear polythene tape coated with acrylic adhesive.

**Applications**

Suitable for use as a splicing tape as well as for industrial and building applications

**Features & Benefits**

Quick and easy to apply

**Application notes**

Apply with a firm pressure to clean, non-porous surfaces. Test an inconspicuous area before use to determine suitability

**Technical Performance**

Description	Units	Value	Test Method
Total thickness	mm	0.120	Digital calliper
Adhesion to steel plate	g/cm	270	-
Tensile strength	Kg/cm	3.3	-
Elongation at break	%	300	-

**Declaration of Conformity Information**

**REACH SVHC Status**

NO SHVC present according to candidates list of the **UK 25/06/20 & EU 14/06/23**

**RoHS Compliance Status**

Not Applicable

**Storage Details**

Shelf life recommended 12 months from date of despatch at the moderate temperature and humidity environment.

The information supplied is accurate to the best of Fosseway Tapes knowledge and is based upon all current data available to it. Properties quoted are typical and do not therefore constitute a specification. Customers must complete their own assessment of the product for its intended application under their own conditions. Our technical advice is to be regarded as an expression of opinion only and although such advice is given in good faith, it shall not, in any circumstances, be regarded as the basis of or as being a representation or statement of fact. This applies also where propriety or protective rights of third parties are involved. Any liability arising in respect of our products will be strictly limited to the value of those products charged to the customer and shall not extend to any consequential loss whatsoever and howsoever arising. This document does not form part of any contract with a customer (02/05/13)